

May 2013



Unit 2, 21 Penny Place, Arndell Park NSW 2148.

Phone (02) 8678 4029
sales@lnc.net.au

Fax (02) 8678 4059
www.lnc.net.au



LTSS Flexible Liquid Tight 316 Stainless Steel Conduit

Features:

- SS316 stainless steel core, with PVC Jacket.
- PVC jacket conforms with UL360.
- Flame retardant, oil and sunlight resistant.
- High flexibility, liquid tight.
- Corrosion and rust resistant.
- Temperature rating -20 C to +70 C
- RoHS compliant.
- IP67
- Cord pack sizes from 3/8" to 1 1/4" by square locked. 1 1/2" to 4" by interlocked.

Application:

Product absorbs movement and vibration with indefinite bending ability.
Extreme corrosion resistance.
Used with installations of automatic machinery.

Part Number	Nominal size (inch)	Min. Inner Diameter (mm)	Max Inner Diameter (mm)	Min Outside Diameter (mm)	Max Outside Diameter (mm)	Min Bending Radius (mm)	Pack Length
LTSS016-B-25	3/8"	12.3	12.8	17.5	18.0	60	25
LTSS020-B-25	1/2"	15.8	16.3	20.8	21.3	80	25
LTSS025-B-25	3/4"	20.7	21.2	26.2	26.7	100	10 and 25
LTSS032-B-25	1"	26.2	26.8	32.7	33.4	150	25