

May 2013



Unit 2, 21 Penny Place, Arndell Park NSW 2148.

Phone (02) 8678 4029
sales@lnc.net.au

Fax (02) 8678 4059
www.lnc.net.au



FSC-SS Flexible Stainless Steel Conduit , 316 Grade

Features:

- SS316 stainless steel core, non liquid tight.
- Light weight, square-locked style.
- Corrosion and rust resistant.
- Small bending radius, high flexibility.
- Flame retardant and anti-interference.
- RoHS compliant.
- IP50

Application:

- Protection of electric wire/ cable and other related products
- Suitable for indoor areas with high temperatures, and is extremely corrosion resistant.
- High flexibility ensures easy installation in tight angled areas.

Part ber	Num- size (inch)	Nominal size (inch)	Min. Inner Diameter (mm)	Max Inner Diameter (mm)	Min Outside Diameter (mm)	Max Outside Diameter (mm)	Min Bending Radius (mm)	Pack Length
FSC16SS-50		16	12.7	13.2	15.7	16.2	33	50
FSC20SS-50		20	16.7	17.2	20.1	20.6	38	50
FSC25SS-50		25	20.8	21.3	24.6	25.1	45	50
FSC32SS-50		32	27.8	28.4	32.0	32.6	55	50
FSC40SS-50		40	37.4	38.0	42.2	42.8	62	50
FSC50SS-20		50	48.1	48.7	52.9	53.5	110	20