

VJCLFH RANGE - LOW FIRE HAZARD - POLYURETHANE VACUUM JACKETED HOT DIPPED GALVANISED STEEL FLEXIBLE CONDUIT .

Product ID: **VJCLFH LOW SMOKE/HALOGEN FREE FLEXIBLE CONDUIT**

TECHNICAL FEATURES: LOW FIRE HAZARD FLEXIBLE CONDUIT

- Hot Dipped Galvanized steel core with thermoplastic Polyurethane jacket.
- TPU jacket conforms with UL 360 that is flame retardant.
- Liquid tight flexible conduit - **LOW SMOKE – HALOGEN FREE** U2017
- Oil resistant . (conforms with UL 360)
- Light weight style, excellent flexibility and liquid-tightness.
- Use for railway & road tunnels , hospitals , shopping malls , and where public safety is a concern in respect to fire protection etc.
- Temperature rating: -40C ~ +80C.
- Standard colour: black.
- IP65 used with C type fittings .
- RoHS & REACH Compliant .
- Compression Strength- 350KG/100MM



TECHNICAL DIMENSIONS

CATALOGUE NUMBER	NOMINAL SIZE	I.D.(mm)	O.D. (mm)	MIN. BENDING RADIUS (mm)	REEL LENGTHS (MTRES)
VJCLFH016BK-50	M16	12.50	17.00	40.00	50/25/10
VJCLFH020BK-50	M20	16.00	20.50	45.00	50/25/10
VJCLFH025BK-50	M25	21.00	25.80	55.00	50/25/10
VJCLFH032BK-50	M32	26.30	31.90	60.00	50/25/10
VJCLFH040BK-30	M40	35.00	41.10	80.00	30/10
VJCLFH050BK-30	M50	40.30	46.90	90.00	20/10
VJCLFH063BK-20	M63	51.60	58.40	115.00	20/10