

## CB Series – Conduit Coupling Sleeve (Nickel Plated Brass)

- Nickel Plated Brass conduit coupling sleeve (also available in 316 Stainless Steel)
- Precision engineered – designed for use in weatherproof and harsh environments.
- Ideal for installation in Marine / Offshore environments, Food, Beverage and Pharmaceutical industries

### Product Details:

- Temperature range - -40°C Min to + 110°C Max
- Material - Nickel plated brass
- IP Protection - IP66 / IP67 / IP68
- Characteristics - Brass outer body with metric internal thread
- Applications - Designed for joining two metallic conduits together  
- Marine / Offshore  
- Food and beverage  
- Pharmaceuticals



Product Catalogue No.	Nominal Conduit Size (mm)	Internal Thread size (mm)	Length (mm)	External Diameter (mm)	Nominal Thickness (mm)
CB16	16	M16 x 1.5	25.0	20.0	2.00
CB20	20	M20 x 1.5	30.0	24.5	3.00
CB25	25	M25 x 1.5	36.0	28.5	2.50
CB32	32	M32 x 1.5	32.0	38.5	2.50
CB40	40	M40 x 1.5	65.0	47.0	4.00
CB50	50	M50 x 1.5	70.0	57.0	4.00

*Last Updated: 27/01/2026*