

EMC Metal Cable Gland (Nickel Plated Brass)

- Nickel Plated Brass EMC Cable Glands
- When used with appropriate shielded cable, the L&C EMC fitting provides protection from the effects of electromagnetic interference (EMI).

Product Details:

Temperature range	- -40°C Min to + 100°C Max (Short term: 120°C)
Material	- Nickel Plated Brass
Thread Seal	- Nitrile Butadiene Rubber (NBR)
Cable Clamp & Seal	- PA6 Cable Clamp with NBR cable seal insert
IP Protection	- IP66/IP67/IP68 <small>Note 1</small>
Characteristics	- Multi-part component fitting - NBR Thread sealing washer supplied with fitting

Note:

- Lock rings to suit the EMC Cable Glands are not supplied with this fitting.
- Lock rings must be ordered separately. Please refer below table for relevant part number.



Product Catalogue No.	Description	Metric Thread Dimensions	Clamping Range (mm)	Thread Length (mm)	Locknut Product Code
EMCMG-20	Brass EMC Cable Gland - M20	M20 X 1.5	9 - 14	10	LNEMC-20
EMCMG-25	Brass EMC Cable Gland - M25	M25 X 1.5	13 - 18	12	LNEMC-25
EMCMG-32	Brass EMC Cable Gland - M32	M32 X 1.5	16 - 24	12	LNEMC-32
EMCMG-40	Brass EMC Cable Gland - M40	M40 X 1.5	22 - 32	12	LNEMC-40
EMCMG-50	Brass EMC Cable Gland - M40	M50 X 1.5	30 - 40	12	LNEMC-50
EMCMG-63	Brass EMC Cable Gland - M50	M63 X 1.5	38 - 53	12	LNEMC-63

Notes:

1. To achieve the stated IP protection rating, the supplied NBR thread sealing washer must be installed.
2. For assistance with installation, please refer to L&C's EMC Assembly instructions (Available on the "Cable Gland" product page on the L&C website at <https://www.lnc.net.au/cable-glands>).