



# CLCMX Series – 45 Degree Nylon Fittings (IP68)

- Black nylon 90 degree fitting with a fixed external male nylon thread and thread sealing washer.
- Designed for terminating CL conduit range (locknut and thread sealing washer supplied).
- Integrated “Quick Release” tab enables fast, snap on installation.

## Product Details:

Temperature range - -40°C to +115°C (150°C Short term)

Material - PA66 Nylon

Colour - Black (RAL 9005)

Protection degree - IP68

*(Note: The supplied thread sealing washer must be installed to achieve IP68 protection rating)*

Characteristics - Low fire hazard, self extinguishing

- UV resistant

- Halogen free, phosphor and cadmium free

- Designed for terminating CL conduit range

Installation - Integrated “quick release” tab enables fast, snap on installation

- Suitable for threaded and knock out entries.

- Locknut and thread sealing washer supplied.



Product Catalogue No.	Thread Dimensions	Nominal CL Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)
CLCMX16-M16-45	M16 X 1.5	16	13.0	23.0	17.0
CLCMX21-M20-45	M20 X 1.5	21	16.0	29.5	17.0
CLCMX28-M25-45	M25 X 1.5	28	22.0	37.0	20.0
CLCMX34-M32-45	M32 X 1.5	34	27.0	44.0	23.0