LT Series Ferrules – Turned-Lip Ferrules (Flared)

- **Turned lip (flared) ferrules available in bare brass, electro-galvanised (zinc plated) steel or 316 stainless steel.**
- **Protects cables from damage when entering and exiting flexible metallic and non-metallic conduits.**
- **Provides maximum protection for electrical installations in Industrial & Commercial environments.**

Product Details:



Temperature range	-	-45°C to + 135°C
Material	-	Bare Brass, Electro-Galvanised (Zinc Plated) Steel or 316 Stainless Steel
Characteristics	-	Turned-lip style with a flared throat
	-	Oil and corrosion resistant
U.V. Protection	-	U.V. Resistant
Compatibility	-	Suitable for all liquid tight flexible conduits made to American (UL360) sizes
Applications	-	Designed to protect cables from damage when entering and exiting flexible metallic conduits, caused by burrs and sharp edges

LT-FL (Zinc Plated Steel)		
L&C Product Code	**Metric Conduit Size (mm)**	**Ferrule Style**
LT-16FL	16	Turned Lip
LT-20FL	20	Turned Lip
LT-25FL	25	Turned Lip
LT-32FL	32	Turned Lip
LT-40FL	40	Turned Lip
LT-50FL	50	Turned Lip
LT-63FL	63	Turned Lip
LT-80FL	80	Turned Lip
LT-100FL	100	Turned Lip

LT-FBL (Nickel Plated Brass)		
L&C Product Code	**Metric Conduit Size (mm)**	**Ferrule Style**
LT-20FBL	20	Turned Lip
LT-25FBL	25	Turned Lip

LT-FLSS (316 Grade Stainless Steel)		
L&C Product Code	**Metric Conduit Size (mm)**	**Ferrule Style**
LT-16FLSS	16	Turned Lip
LT-20FLSS	20	Turned Lip
LT-25FLSS	25	Turned Lip
LT-32FLSS	32	Turned Lip
LT-40FLSS	40	Turned Lip
LT-50FLSS	50	Turned Lip
LT-63FLSS	63	Turned Lip

Last Updated: 29/10/2026