

CL “Cocky Proof” Nylon Conduit

CL “Cocky Proof” Nylon Flexible Conduit

(NOTE: TELSTRA APPROVED FOR BIRD PROOFING)



CONSTRUCTION:

CL conduit is a corrugated medium duty fine pitch polyamide 6 (PA6) nylon flexible conduit. CL conduit is highly flexible with excellent self-recovery. Manufactured to comply with AS/NZS 2053.8:1995.

APPLICATION:

L&C's CL conduit range provides high mechanical protection from bird attack, making it ideal for “bird proofing” an installation and protecting wiring from bird attack.

TECHNICAL PROPERTIES:

- Temperature Rating -40° C to + 105°C (Intermittent to +120°C)
- High U.V. resistance
- High mechanical strength and protection from bird attack
- Highly flexible
- Flame retardant (UL94 V2 tested and certified)
- Halogen free - Self-extinguishing - Flame retardant
- Highly resistant to oils
- High abrasion resistance with a high fatigue life
- High impact strength and self-recovery when crushed
- Fittings: Non-metallic CLCM (IP66) and CLCMX (IP68) range of fittings
- Tensile Strength: 40 kg
- Compression Strength: 36 kg per 100mm (21mm conduit)
- CL conduit range is available in Black (-B) only
- Telstra Approval document available on request
- Minimum Conduit Size Recommended: 25mm (CL025-B)