LT Series Ferrules – Plain Ferrules (Non-Flared Entry)

- **Plain throat, non-flared ferrules available in electro-galvanised (zinc-plated) steel.**
- **Protect cables from damage caused by sharp edges when entering or exiting flexible metallic or non-metallic conduits.**
- **Suitable for use with flexible metallic and non-metallic conduits installed in industrial and commercial environments.**

Product Details:



Temperature range	-	-45°C to + 135°C
Material	-	Electro-Galvanised (Zinc-Plated) Steel
Characteristics	-	Threaded style design with a plain, non-flared entry
	-	Oil and corrosion resistant
UV Protection	-	UV Resistant
Compatibility	-	Suitable for liquid tight flexible metallic conduits made to American (UL360) sizes
Applications	-	Designed to protect cables from damage caused by burrs and sharp conduit edges when entering and exiting flexible conduits

L&C Product Code	Metric Conduit Size (mm)	Ferrule Style
LT-16F	16	Plain, Non-Flared Entry
LT-20F	20	Plain, Non-Flared Entry
LT-25F	25	Plain, Non-Flared Entry
LT-32F	32	Plain, Non-Flared Entry
LT-40F	40	Plain, Non-Flared Entry
LT-50F	50	Plain, Non-Flared Entry
LT-63F	63	Plain, Non-Flared Entry
LT-75F	75	Plain, Non-Flared Entry
LT-80F	80	Plain, Non-Flared Entry
LT-100F	100	Plain, Non-Flared Entry

Last Updated: 03/11/2026