

CLCM Series – Straight Nylon Fittings

- Black nylon straight fitting with a fixed external male nylon thread.
- Designed for terminating CL conduit range (locknut supplied).
- Integrated “Quick Release” tab enables fast, snap on installation.

Product Details:

Temperature range	- -40°C to + 115°C (Short term 150°C)
Material	- PA66 Nylon
Colour	- Black (RAL 9005)
Protection degree	- IP66
U.V. Rating	- U.V. resistant and suitable for outdoor use.
Characteristics	- Low fire hazard, flame retardent, self extinguishing - Halogen free - Free of Phosphor and cadmium - Designed for terminating CL conduit range
Installation	- Integrated “quick release” tab enables fast, snap on installation - No tools required - Suitable for threaded and knock out entries. Locknut supplied.



Product Catalogue No	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length(mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
CLCM10-M12	M12 X 1.5	16	11.5	10	17	34.5
CLCM10-M16	M16 X 1.5	16	11.5	13	20	36.5
CLCM13-M12	M12 X 1.5	16	11.5	10	17	34.5
CLCM13-M16	M16 X 1.5	16	11.5	13	20	36.5
CLCM16-M16	M16 X 1.5	16	12	13	23	39.5
CLCM16-M20	M16 X 1.5	16	12	16	23	39.5
CLCM20-M20	M20 X 1.5	16	13	16	29.5	45.0
CLCM21-M20	M20 X 1.5	20	13	16	29.5	45.0
CLCM25-M25	M25 X 1.5	25	13	22	37	47.0
CLCM28-M25	M25 X 1.5	25	13	22	37	47.0
CLCM34-M32	M32 X 1.5	32	15	27	44	51.0
CLCM42-M40	M40 X 1.5	40	15	35	52	54.0
CLCM54-M50	M50 X 1.5	50	16	45	64	55.0
CLCM54-M63	M63 X 1.5	63	16	55	64	55.0
CLCM67-M63	M63 X 1.5	63	16	65	89	71.0