



## LC-FH Series – Female Hub Fittings (316 Stainless Steel)

- **316 Marine Grade Stainless Steel straight fittings** (also available in Zinc Die cast and Nickel Plated Brass)
- **Provides maximum protection for electrical installations in Industrial & Commercial environments.**

### Product Details:

- Temperature range - -45°C to + 135°C
- Material - 316 Marine Grade Stainless Steel
- Protection degree - IP66/IP67/IP68 <sup>Note 1</sup>
- U.V. Rating - U.V. resistant and suitable for outdoor use.
- Characteristics - High tensile strength, oil resistant, corrosion resistant  
- Multi-part compression fitting with a female metric thread
- Compatibility - Interchangeable with all liquid tight conduits made to American (UL360) sizes.
- Applications - Suitable for threaded and knock out entries.



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)	Back Nut Torque Tension Required (Nm) <sup>Note 2</sup>
LC-16-FH-SS	M16 X 1.5	16	16.5	10.4	28	33	22.6 Nm
LC-16/20-FH-SS	M20 X 1.5	16	16.5	13.5	28	34	33.9 Nm
LC-20-FH-SS	M20 X 1.5	20	17.0	13.5	32	35	33.9 Nm
LC-25-FH-SS	M25 X 1.5	25	17.5	18.5	37	37	56.5 Nm
LC-40-FH-SS	M40 X 1.5	40	18.0	33.4	56	50	113 Nm

### Notes:

1. To achieve IP 66/67/68 protection for this fitting, a thread sealing washer or O ring must be installed.
2. The back nut, which clamps the flexible conduit to the fitting, must be tightened to the torque tension stated to achieve the IP protection rating of the fitting and prevent water ingress.