

## Type – NMFG Conduit

### Flexible Food Grade Non-Metallic Conduit



#### CONSTRUCTION:

Type NMFG consists of a spiral rigid PVC inner core embedded within a flexible non-metallic PVC wall. The smooth exterior makes for an easy wash down. This conduit is resistant to bleach (sodium hypochlorite) and does not promote bacteria growth.

L&C Product Code	Nominal Size mm	Internal Diameter (mm)		Outer Diameter (mm)		Inside Bend Radius (mm)	Wt. Kgs. Per 30 Mtrs.	Coil Length (Mtr)
		Min.	Max.	Min.	Max.			
NMFG-016-W-30	16	12.3	12.8	17.5	18	51	4.5	30
NMFG-020-W-30	20	15.8	16.3	20.8	21.3	82	5	30
NMFG-025-W-30	25	20.8	21.3	26.2	26.7	108	7	30
NMFG-032-W-30	32	26.4	27.1	32.8	33.4	165	11	30
NMFG-040-W-30	40	35.1	35.8	41.4	42.2	203	15	30
NMFG-050-W-15	50	40	40.6	47.4	48.3	229	19	15

#### APPLICATION:

Type NMFG is suitable for use in splash zone food and beverage environments. NMFG is also suitable for use in a variety of wiring applications involving the connection of food processing equipment or clean room installations where motion, vibration and bending occurs.

#### CHARACTERISTICS:

- Temperature Rating -20° C to + 80°C
- Oil and bleach resistant
- Excellent flexibility
- Standard colour is white
- Fittings: Non-metallic IP67 range of NMCM fittings and metallic LC conduit fittings