

VJCF Series – Straight Swivel Fittings (Brass)

- Two (2) component nickel plated brass straight non-compression swivel fitting.
- Provides maximum protection for electrical installations in Industrial & Commercial environments.

Product Details:

- Temperature range - -45°C to + 135°C
- Material - Nickel Plated Brass
- Protection degree - IP54
- Characteristics - High tensile strength, oil resistant, corrosion resistant
- Multi-part two (2) component non-compression fitting
- External male metric thread
- Compatibility - Interchangeable and adaptable with Adaptaflex SP and Flexicon FSU ranges
- Applications - Suitable for threaded and knock out entries.



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
VJCF16-B-SW	M16 X 1.5	16	12.7	10.4	28	36.7
VJCF20-B-SW	M20 X 1.5	20	12.7	13.5	32	36.7
VJCF25-B-SW	M25 X 1.5	25	14.2	18.5	39	39.3
VJCF32-B-SW	M32 X 1.5	32	16.3	24.9	47	43.3
VJCF40-B-SW	M40 X 1.5	40	18.2	33.4	60	51.2
VJCF50-B-SW	M50 X 1.5	50	18.2	37.8	67	51.2
VJCF63-B-SW	M63 X 1.5	63	20.0	48.6	81	54.0