



CSS Series – Conduit Coupling Sleeve (Stainless Steel)

- **316 Marine Grade Stainless Steel conduit coupling sleeve** (also available in Nickel Plated Brass)
- **Precision engineered from 316 Stainless steel – designed for use in weatherproof and harsh environments.**
- **Ideal for installation in Marine / Offshore environments, Food, Beverage and Pharmaceutical industries**

Product Details:

- Temperature range - -40°C Min to + 110°C Max
- Material - 316 marine grade stainless steel body
- IP Protection - IP66 / IP67 / IP68
- Characteristics - Stainless steel outer body with metric internal thread
- Applications - Designed for joining two metallic conduits together
- Marine / Offshore
 - Food and beverage
 - Pharmaceuticals



Product Catalogue No.	Nominal Conduit Size (mm)	Internal Thread size (mm)	Length (mm)	External Diameter (mm)	Nominal Thickness (mm)
CSS20	20	M20 x 1.5	34.0	25.0	2.00
CSS25	25	M25 x 1.5	39.0	28.5	2.50
CSS32	32	M32 x 1.5	45.0	38.5	4.00
CSS40	40	M40 x 1.5	30.0	45.0	2.75
CSS50	50	M50 x 1.5	35.0	55.0	2.75
CSS63	63	M63 x 1.5	42.0	70.0	3.25

Last Updated: 27/01/2026