



NMCM Series – Straight Nylon Fitting (IP67)

- Two part nylon compression fitting.
- External metric thread complete with locknut
- Designed for terminating NM conduit range

Product Details:

Temperature range	- -50°C to + 135°C (Short term 150°C)
Material	- PA66 Nylon
Colour	- Black (RAL 9005)
Protection degree	- IP67
U.V. Rating	- U.V. resistant and suitable for outdoor use.
Chemical Resistance	- Oil and corrosion resistant
Characteristics	- Low fire hazard - Designed for terminating NM conduit range
Installation	- Two part compression nylon fitting with external metric thread - Suitable for knock out or threaded entries - Locknut supplied



L&C Product Code	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
NMCM-16	M16 X 1.5	16	11	11.0	26.5	39.0
NMCM-16/20	M20 X 1.5	16	14	11.0	33.5	39.0
NMCM-20	M20 X 1.5	20	14	13.0	33.5	47.5
NMCM-25	M25 X 1.5	25	15	18.0	41.5	49.0
NMCM-32	M32 X 1.5	32	16	25.0	48.5	56.0
NMCM-40	M40 X 1.5	40	16	32.0	59.5	62.0
NMCM-50	M50 X 1.5	50	19	37.0	65.0	65.0
NMCM-63	M63 X 1.5	63	21	48.0	80.0	70.5

Last Updated: 02/10/2025