

Type – NM2 Conduit

Highly Flexible Non-Metallic Liquid Tight Conduit



CONSTRUCTION:

Type NM2 conduit is a highly flexible liquid tight non-metallic conduit. NM2 is helically wound with a spiral of rigid PVC reinforcement embedded within the flexible PVC wall. Manufactured to comply with AS/NZS 2053.8:1995.

L&C Product Code	Nominal Size mm	Internal Diameter (mm)		Outer Diameter (mm)		Inside Bend Radius (mm)	Weight (Kgs) Per 30 Metres	Roll Length (Mtr)
		Min.	Max.	Min.	Max.			
NM2012-B-30	12	9.8	10.3	11.8	12.3	-	-	30
NM2016-B-30	16	12.3	12.8	17.5	18	17	3	30
NM2020-B-30	20	15.8	16.3	20.8	21.3	23	4	30
NM2025-B-30	25	20.8	21.3	26.2	26.7	28	5	30
NM2032-B-30	32	26.4	27.1	32.8	33.4	33	7	30
NM2040-B-30	40	35.1	35.8	41.4	42.2	43	9	30
NM2050-B-15	50	40.0	40.6	47.4	48.3	48	12	15
NM2063-B-15	63	51.3	51.9	59.4	60.3	61	16	15

APPLICATION:

Type NM2 flexible non-metallic conduit is ideal for use in machine wiring, security wiring installations and many other industrial applications.

CHARACTERISTICS:

- Temperature Rating -20° C to + 70°C
- Fittings: Non-metallic IP65 range NMCM range of fittings only
- Tensile Strength: 25 kg
- Compression Strength: 60 kg per 100mm
- Type NM2 conduit is only available in Black (-B)