


7.9mm 316 Stainless Steel Cable Ties (Epoxy Coated)

CONSTRUCTION:

- Manufactured from high-tensile 316-grade AISI stainless steel
- 7.9 mm ball-lock cable tie
- 316 stainless steel cable ties with a full epoxy coating
- Manufactured with a unique ball-locking mechanism
- Enables simple and rapid installation with secure locking
- Burr-free with smooth edges



TECHNICAL DETAIL:

- Thickness: 0.25 mm (± 0.01 mm)
- Width: 7.9 mm
- Head:
 - L1 = 13.5 mm
 - W1 = 10.5 mm
 - H = 5.5 mm
- Ball: 316-grade stainless steel
- Ball Diameter: 3.18 mm
- Minimum Loop Tensile Strength: 1115 N
- Coating: Full epoxy coating
- Colour: Black

L&C Product Code	Locking Mechanism	External Finish	Width (W) (mm)	Stainless Steel Grade	Length (L) (mm)	Maximum Bundle Diameter (mm)	Minimum Loop Tensile Strength (N)
CTSS200-7.9BK316-100	Ball Locking	Epoxy Coated	7.9	316	200	50	1115
CTSS300-7.9BK316-100	Ball Locking	Epoxy Coated	7.9	316	300	85	1115
CTSS360-7.9BK316-100	Ball Locking	Epoxy Coated	7.9	316	360	100	1115
CTSS520-7.9BK316-100	Ball Locking	Epoxy Coated	7.9	316	520	155	1115

APPLICATION:

- CTSS epoxy coated cable ties are ideal for use in industrial and commercial installations in both internal and external environments including solar farms and tunnel environments.
- Suitable for use in harsh environments.

CHARACTERISTICS:

- Temperature Rating: -80°C to +150°C
- Resistant to oils, mild acids and many industrial chemicals
- Weather and sunlight (UV) resistant

Last Updated: 18/08/2026