



LT Series Ferrules – Turned-Lip Ferrules (Flared)

- Turned lip (flared) ferrules available in bare brass, electro-galvanised (zinc plated) steel or 316 stainless steel.
- Protects cables from damage when entering and exiting flexible metallic and non-metallic conduits.
- Provides maximum protection for electrical installations in Industrial & Commercial environments.

Product Details:

- Temperature range - -45°C to + 135°C
- Material - Bare Brass, Electro-Galvanised (Zinc Plated) Steel or 316 Stainless Steel
- Characteristics - Turned-lip style with a flared throat
- Oil and corrosion resistant
- U.V. Protection - U.V. Resistant
- Compatibility - Suitable for all liquid tight flexible conduits made to American (UL360) sizes
- Applications - Designed to protect cables from damage caused by burrs and sharp edges when entering and exiting flexible metallic conduits



LT-FL (Zinc Plated Steel)		
Product Catalogue No.	Metric Conduit Size (mm)	Ferrule Style
LT-16FL	16	Turned Lip
LT-20FL	20	Turned Lip
LT-25FL	25	Turned Lip
LT-32FL	32	Turned Lip
LT-40FL	40	Turned Lip
LT-50FL	50	Turned Lip
LT-63FL	63	Turned Lip
LT-80FL	80	Turned Lip
LT-100FL	100	Turned Lip

LT-FBL (Nickel Plated Brass)		
Product Catalogue No.	Metric Conduit Size (mm)	Ferrule Style
LT-16FBL	16	Turned Lip
LT-20FBL	20	Turned Lip
LT-25FBL	25	Turned Lip
LT-32FBL	32	Turned Lip
LT-40FBL	40	Turned Lip
LT-50FBL	50	Turned Lip

LT-FLSS (316 Grade Stainless Steel)		
Product Catalogue No.	Metric Conduit Size (mm)	Ferrule Style
LT-16FLSS	16	Turned Lip
LT-20FLSS	20	Turned Lip
LT-25FLSS	25	Turned Lip
LT-32FLSS	32	Turned Lip
LT-40FLSS	40	Turned Lip
LT-50FLSS	50	Turned Lip
LT-63FLSS	63	Turned Lip