



CB Series – Conduit Coupling Sleeve (Nickel Plated Brass)

- Nickel Plated Brass conduit coupling sleeve (also available in 316 Stainless Steel)
- Precision engineered – designed for use in weatherproof and harsh environments.
- Ideal for installation in Marine / Offshore environments, Food, Beverage and Pharmaceutical industries

Product Details:

- Temperature range - -40°C Min to + 110°C Max
- Material - Nickel plated brass
- IP Protection - IP66 / IP67 / IP68
- Characteristics - Brass outer body with metric internal thread
- Applications - Designed for joining two metallic conduits together
- Marine / Offshore
 - Food and beverage
 - Pharmaceuticals



| Product Catalogue No. | Nominal Conduit Size (mm) | Internal Thread size (mm) | Length (mm) | External Diameter (mm) |
|-----------------------|---------------------------|---------------------------|-------------|------------------------|
| CB16 | 16 | M16 x 1.5 | 25.0 | 20.0 |
| CB20 | 20 | M20 x 1.5 | 30.0 | 24.5 |
| CB25 | 25 | M25 x 1.5 | 36.0 | 28.5 |
| CB32 | 32 | M32 x 1.5 | 32.0 | 38.5 |
| CB40 | 40 | M40 x 1.5 | 65.0 | 47.0 |
| CB50 | 50 | M50 x 1.5 | 70.0 | 57.0 |
| CB63 | 63 | M63 x 1.5 | 70.0 | 70.0 |