



NMCM Series – Straight Nylon Fitting (IP67)

- Two part nylon compression fitting.
- External metric thread complete with locknut
- Designed for terminating NM conduit range

Product Details:

- Temperature range - -50°C to + 135°C (Short term 150°C)
- Material - PA66 Nylon
- Colour - Black (RAL 9005)
- Protection degree - IP67
- U.V. Rating - U.V. resistant and suitable for outdoor use.
- Chemical Resistance - Oil and corrosion resistant
- Characteristics - Low fire hazard
- Designed for terminating NM conduit range
- Installation - Two part compression nylon fitting with external metric thread
- Suitable for knock out or threaded entries
- Locknut supplied



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
NMCM-16	M16 X 1.5	16	11	11.0	26.5	39.0
NMCM-16/20	M20 X 1.5	16	14	11.0	33.5	39.0
NMCM-20	M20 X 1.5	20	14	13.0	33.5	47.5
NMCM-25	M20 X 1.5	25	15	18.0	41.5	49.0
NMCM-32	M25 X 1.5	32	16	25.0	48.5	56.0
NMCM-40	M32 X 1.5	40	16	32.0	59.5	62.0
NMCM-50	M40 X 1.5	50	19	37.0	65.0	65.0
NMCM-63	M50 X 1.5	63	21	48.0	80.0	70.5