



CLCMX Series – Straight Female Hub Nylon Fittings (IP68)

- Black nylon straight fitting with an internal female nylon thread.
- Designed for terminating CL conduit range.
- Integrated “Quick Release” tab enables fast, snap on installation.

Product Details:

- Temperature range - -40°C to +115°C (150°C Short term)
- Material - PA66 Nylon
- Colour - Black (RAL 9005)
- Protection degree - IP68
- Characteristics - Low fire hazard, self extinguishing
 - UV resistant
 - Halogen free, phosphor and cadmium free
 - Designed for terminating CL conduit range
- Installation - Integrated “quick release” tab enables fast, snap on installation



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
CLCMX13-F16	M16 X 1.5	13.0	13.5	10.0	20.0	38.0
CLCMX16-F16	M16 X 1.5	15.8	13.5	12.0	23.0	41.0
CLCMX21-F20	M20 X 1.5	21.2	13.5	17.0	29.5	47.0
CLCMX28-F25	M25 X 1.5	28.5	16.0	23.5	37.0	50.0
CLCMX34-F32	M32 X 1.5	34.5	17.5	30.0	44.0	56.0