



CLCMX-BM – Straight Nylon Brass Fitting (IP68)

- Black nylon straight fitting with a nickel plated brass external male thread.
- Designed for terminating CL conduit range (thread sealing O ring supplied).
- Integrated “Quick Release” tab enables fast, snap on installation.

Product Details:

- Temperature range - -40°C to +115°C (150°C Short term)
- Material - PA66 Nylon
- Colour - Black (RAL 9005)
- Protection degree - IP68
- (Note: The supplied thread sealing “O” ring must be installed to achieve IP68 protection rating)*
- Characteristics - Low fire hazard, self extinguishing
 - UV resistant
 - Halogen free, phosphor and cadmium free
 - Designed for terminating CL conduit range
- Installation - Integrated “quick release” tab enables fast, snap on installation
 - Suitable for threaded and knock out entries.
 - Thread sealing O ring supplied



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
CLCMX10-BM12	M12 X 1.5	10	10	7.0	17.0	34.5
CLCMX13-BM16	M16 X 1.5	13	12	10.0	20.0	36.5
CLCMX16-BM16	M16 X 1.5	16	12	10.0	23.0	39.5
CLCMX21-BM20	M20 X 1.5	21	12	15.0	29.5	45.0
CLCMX28-BM25	M25 X 1.5	28	13	18.0	37.0	47.0
CLCMX34-BM32	M32 X 1.5	34	14	24.0	44.0	51.0
CLCMX42-BM40	M40 X 1.5	42	17	32.0	52.0	54.0
CLCMX54-BM50	M50 X 1.5	54	17	43.0	64.0	55.0