

CLCMX-CGB – Straight Nylon Cable Gland Fittings (IP68)

- One piece black nylon straight fitting with an external threaded cable gland.
- Designed for terminating CL conduit range (locknut supplied).
- Integrated “Quick Release” tab enables fast, snap on installation.

Product Details:

Temperature range	-	-40°C to +105°C (150°C Short term)
Material	-	PA66 Nylon
Colour	-	Black (RAL 9005)
Protection degree	-	IP68
Chemical Resistance	-	Oil and corrosion resistant
Characteristics	-	Low fire hazard, self extinguishing
	-	UV resistant
	-	Halogen free, phosphor and cadmium free
	-	Designed for terminating CL conduit range
Installation	-	Integrated “quick release” tab enables fast, snap on installation
	-	Suitable for threaded and knock out entries
	-	Locknut supplied



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Clamping Range (mm)
CLCMX10-M12-CGB	M10 X 1.5	12	8.0	10.0	3 - 6.5
CLCMX13-M16-CGB	M13 X 1.5	16	8.0	13.0	4 - 8
CLCMX16-M16-CGB	M16 X 1.5	16	15.0	13.0	6 - 10
CLCMX21-M20-CGB	M20 X 1.5	20	15.0	16.0	10 - 14
CLCMX28-M25-CGB	M25 X 1.5	25	14.0	16.0	14 - 18
CLCMX34-M32-CGB	M32 X 1.5	32	12.0	16.0	18 - 25
CLCMX42-M40-CGB	M40 X 1.5	40	13.0	22.0	24 - 32
CLCMX54-M50-CGB	M50 X 1.5	50	14.0	22.0	30 - 38