



LT Series Ferrules – Plain Ferrules (Non-Flared)

- Plain throat, non-flared ferrules available in bare brass or electro-galvanised (zinc plated) steel.
- Protects cables from damage when entering and exiting flexible metallic and non-metallic conduits.
- Provides maximum protection for electrical installations in Industrial & Commercial environments.

Product Details:

- Temperature range - -45°C to + 135°C
- Material - Bare Brass or Electro-Galvanised (Zinc Plated) Steel
- Characteristics - Threaded style, non flared
- Oil and corrosion resistant
- U.V. Protection - U.V. Resistant
- Compatibility - Suitable for all liquid tight flexible conduits made to American (UL360) sizes
- Applications - Designed to protect cables from damage caused by burrs and sharp edges when entering and exiting flexible conduits



LT-F (Zinc Plated Steel)		
Product Catalogue No.	Metric Conduit Size (mm)	Ferrule Style
LT-16F	16	Plain
LT-20F	20	Plain
LT-25F	25	Plain
LT-32F	32	Plain
LT-40F	40	Plain
LT-50F	50	Plain
LT-63F	63	Plain
LT-75F	75	Plain
LT-80F	80	Plain
LT-100F	100	Plain

LT-FB (Nickel Plated Brass)		
Product Catalogue No.	Metric Conduit Size (mm)	Ferrule Style
LT-16FB	16	Plain
LT-20FB	20	Plain
LT-25FB	25	Plain
LT-32FB	32	Plain
LT-40FB	40	Plain
LT-50FB	50	Plain
LT-63FB	63	Plain