LT Series Ferrules – Turned Lip (Flared Entry)

- **Turned-lip (flared) ferrules are available in bare brass, electro-galvanised (zinc-plated) steel and 316 stainless steel.**
- **Protect cables from damage caused by sharp edges when entering or exiting flexible metallic conduits.**
- **Suitable for use with flexible metallic conduits installed in industrial and commercial environments.**

Product Details:



Temperature range - -45°C to + 135°C

Material - Bare Brass, Electro-Galvanised (Zinc-Plated) Steel or 316 Stainless Steel

Characteristics - Turned-lip design with a flared entry
- Oil and corrosion resistant

UV Protection - UV Resistant

Compatibility - Suitable for liquid tight flexible metallic conduits made to American (UL360) sizes

Applications - Designed to protect cables from damage caused by burrs and sharp conduit edges when entering and exiting flexible metallic conduits

LT-FL (Zinc Plated Steel)		
L&C Product Code	**Metric Conduit Size (mm)**	**Ferrule Style**
LT-16FL	16	Turned Lip Entry
LT-20FL	20	Turned Lip Entry
LT-25FL	25	Turned Lip Entry
LT-32FL	32	Turned Lip Entry
LT-40FL	40	Turned Lip Entry
LT-50FL	50	Turned Lip Entry
LT-63FL	63	Turned Lip Entry
LT-80FL	80	Turned Lip Entry
LT-100FL	100	Turned Lip Entry

LT-FBL (Bare Brass)		
L&C Product Code	**Metric Conduit Size (mm)**	**Ferrule Style**
LT-20FBL	20	Turned Lip Entry
LT-25FBL	25	Turned Lip Entry

LT-FLSS (316 Grade Stainless Steel)		
L&C Product Code	**Metric Conduit Size (mm)**	**Ferrule Style**
LT-16FLSS	16	Turned Lip Entry
LT-20FLSS	20	Turned Lip Entry
LT-25FLSS	25	Turned Lip Entry
LT-32FLSS	32	Turned Lip Entry
LT-40FLSS	40	Turned Lip Entry
LT-50FLSS	50	Turned Lip Entry
LT-63FLSS	63	Turned Lip Entry

Last Updated: 03/11/2026