

CLL Contractor Pack

CLL Contractor Pack



CONTENTS:

- 10 Metre roll of CLL light duty fine pitch polyamide 6 (PA6) nylon flexible conduit
- 10 Each – CLCM IP66 Polyamide 66 Nylon black snap-on quick release straight connectors

L&C Product Code	CLL Conduit Details	Nominal Size (mm)	Internal Diameter (mm)	Outside Diameter (mm)	Minimum Bending Radius (mm)	Roll Length (Mtr)	CLCM Terminator	IP Rating	Thread Dimensions
CLL016-CP	CLL016	16	12.0	15.8	35	10	CLCM16-M16	IP66	M16 X 1.5
CLL020-CP	CLL020	20	15.0	20.0	40	10	CLCM20-M20	IP66	M20 X 1.5
CLL021-CP	CLL021	20	16.9	21.2	40	10	CLCM21-M20	IP66	M20 X 1.5
CLL025-CP	CLL025	25	19.3	25.0	45	10	CLCM25-M25	IP66	M25 X 1.5
CLL028-CP	CLL028	25	23.0	28.5	45	10	CLCM28-M25	IP66	M25 X 1.5

TECHNICAL CHARACTERISTICS (CLL Conduit):

- Temperature Rating -40° C to + 105°C (intermittent exposure to +120°C)
- Highly flexible and abrasion resistant with a high fatigue life
- Highly resistant to oils and solvents
- Halogen free and self-extinguishing
- Flame retardant, low smoke
- High impact and UV resistant
- Sunlight resistant
- Light in weight with a high impact strength and good recovery if crushed
- Fittings: CLL Conduit uses non-metallic CLCM (IP66) and CLCMX (IP68) range of fittings