

## CLCMX Series – Straight Nylon Fittings (IP68)

- Black nylon straight fitting with a fixed external male nylon thread and thread sealing washer.
- Designed for terminating CL conduit range (locknut and thread sealing washer supplied).
- Integrated “Quick Release” tab enables fast, snap on installation.

### Product Details:

- Temperature range - -40°C to +115°C (150°C Short term)
- Material - PA66 Nylon
- Colour - Black (RAL 9005)
- Protection degree - IP68  
*(Note: The supplied thread sealing washer must be installed to achieve IP68 protection rating)*
- Characteristics - Low fire hazard, self extinguishing  
- UV resistant  
- Halogen free, phosphor and cadmium free  
- Designed for terminating CL conduit range
- Installation - Integrated “quick release” tab enables fast, snap on installation  
- Suitable for threaded and knock out entries.  
- Locknut supplied.



Product Catalogue No.	Thread Dimensions	Nominal Conduit Size (mm)	Thread Length (mm)	Inside Diameter (mm)	Outside Diameter (mm)	Total Length (mm)
CLCMX10-M12	M12 X 1.5	10	11.5	10.0	17.0	34.5
CLCMX13-M12	M13 X 1.5	13	11.5	13.0	20.0	36.5
CLCMX16-M16	M16 X 1.5	16	12.0	13.0	23.0	39.5
CLCMX16-M20	M16 X 1.5	16	12.0	16.0	23.0	39.5
CLCMX20-M20	M20 X 1.5	20	13.0	16.0	29.5	45.0
CLCMX21-M20	M20 X 1.5	20	13.0	16.0	29.5	45.0
CLCMX25-M25	M25 X 1.5	25	13.0	22.0	37.0	47.0
CLCMX28-M25	M25 X 1.5	28	13.0	22.0	37.0	47.0
CLCMX34-M32	M32 X 1.5	34	15.0	27.0	44.0	51.0
CLCMX42-M40	M40 X 1.5	42	15.0	35.0	52.0	54.0
CLCMX54-M50	M50 X 1.5	50	16.0	45.0	64.0	55.0